

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

ATTORNEY DOCKET NO. 048369/0118

Applicant: Hirofumi KAMOSAWA et al.

Title: LIQUID-CRYSTAL DISPLAY ELEMENT AND METHOD FOR
MANUFACTURING SAME

Appl. No.: Unassigned

Filing Date: 07/21/2000

Examiner: Unassigned

Art Unit: Unassigned

UTILITY PATENT APPLICATION
TRANSMITTAL

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. § 1.53(b) is the nonprovisional
utility patent application of:

Hirofumi KAMOSAWA
Takeya SHIMIZU

Enclosed are:

- [X] Specification, Claim(s), and Abstract (15 pages).
- [X] Formal drawings (7 sheets, Figures 1-7).
- [X] Declaration and Power of Attorney (2 pages).
- [X] Assignment of the invention to NEC CORPORATION.
- [X] Assignment Recordation Cover Sheet.
- [X] Claim for Convention Priority and Priority Document.
- [X] Information Disclosure Statement.
- [X] Form PTO-1449 with copies of 6 listed reference(s).

Appl. No. Unassigned

The filing fee is calculated below:

	Claims as Filed	Included in Basic Fee	Extra Claims	Rate	Fee Totals
Basic Fee				\$690.00	\$690.00
Total Claims:	11	- 20	= 0	x \$18.00	= \$0.00
Independents:	3	- 3	= 0	x \$78.00	= \$0.00
If any Multiple Dependent Claim(s) present:			+	\$260.00	= \$0.00
Assignment Recordation Sheet			+	\$40.00	= \$40.00
				SUBTOTAL:	= \$730.00
[] Small Entity Fees Apply (subtract ½ of above):					= \$0.00
				TOTAL FILING FEE:	= \$730.00

- [X] A check in the amount of \$730.00 to cover the filing fee is enclosed.
- [] The required filing fees are not enclosed but will be submitted in response to the Notice to File Missing Parts of Application.
- [X] The Assistant Commissioner is hereby authorized to charge any additional fees which may be required regarding this application under 37 C.F.R. §§ 1.16-1.17, or credit any overpayment, to Deposit Account No. 19-0741. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Assistant Commissioner is authorized to charge the unpaid amount to Deposit Account No. 19-0741.

Please direct all correspondence to the undersigned attorney or agent at the address indicated below.

Respectfully submitted,

July 21, 2000
Date

Aaron C. Leattage
for David A. Blumenthal Reg # 41,398
Attorney for Applicant
Registration No. 26,257

FOLEY & LARDNER
Washington Harbour
3000 K Street, N.W., Suite 500
Washington, D.C. 20007-5109
Telephone: (202) 672-5407
Facsimile: (202) 672-5399

SPECIFICATION

Liquid-Crystal Display Element and Method for Manufacturing Same

THE INVENTION

1. Field of the Invention

The present invention relates to a liquid-crystal display element suitable for a thin display having a pair of thin glass substrates, and to a method for manufacturing such a liquid-crystal display element.

2. Description about the Related Art

In liquid-crystal display elements used in displays for notebook personal computers and portable information terminals, in order to achieve a thin and light design, one essential element is to make the thickness of the pair of glass substrates of the liquid-crystal display element thin.

In order to make the thickness of the pair of glass substrates thin, as disclosed, for example, in the Japanese Unexamined Patent Publication (KOKAI) No. 5-61011, a liquid-crystal display element is formed by the process illustrated in Fig. 6.

Specifically, after affixing together an array substrate 10 and an opposing substrate 11, which are the pair of glass substrates, at least one of the array substrate 10 and the opposing substrate 11 is polished (steps 501 and 502). Next, after cutting the array substrate 109 and the opposing substrate 11, a liquid crystal is injected between the array substrate 10 and the opposing substrate 11, this is sealed, and a polarizer is affixed thereto (steps 503 to 506).

The grain diameter used as a polishing material for polishing at least one of the array substrate 10 and the opposing substrate 11 is approximately 1 to 2 μ m.

For this reason, the polishing material intrudes into the space (5 to 6 μ m) between the array substrate 10 and the opposing substrate 11, thereby causing failures due to this foreign matter, which lowers the display quality

00521450-072100

and yield of the liquid-crystal display elements.

Given the above, in order to solve the above-noted problem, in the Japanese Unexamined Patent Publications (KOKAI) Nos. 5-249422, 5-249423, and 4-116619, for example, there is disclosure of technology wherein, as shown in Fig. 7, when adhering together the array substrate and the opposing substrate, the liquid crystal injection region of the liquid-crystal display element area is surrounded by a seal 12, and further wherein the entire liquid-crystal display element area is surrounded by an outer peripheral seal 18, after which the hole is sealed by a hole sealant 20.

In this type of technology, because the overall liquid-crystal display element area is surrounded by an outer peripheral seal 18, in above-noted case of performing polishing, intrusion of foreign matter into the space (5 to 6 μ m) between the array substrate 10 and the opposing substrate 11 is prevented.

In the above-noted technology, however, in a method of surrounding the overall liquid-crystal display element area with the outer peripheral seal 18, when cutting apart the individual liquid-crystal display elements the outer peripheral shield 18 is also cut.

For this reason, because the stress on the pair of glass substrates is different between a part at which the outer peripheral seal 18 is cut and a part at which the outer peripheral seal 18 is not cut, thereby causing improper cutting when scribing and breaking.

When the above-noted types of problems occur, polishing material intrudes between the space between the outer peripheral seal 18 and the pair of glass substrates, thereby contaminating the manufacturing apparatus.

If the manufacturing apparatus becomes contaminated in this manner, polishing material can intrude into the liquid-crystal display element when the liquid crystal is injected, leading to improper liquid crystal orientation and faulty operation, such as the proper voltage not being applied between across the liquid crystal, thereby causing a display failure and a drop in yield.

09624450-072100

Accordingly, it is an object of the present invention, in consideration of the above-noted problems, to provide a liquid-crystal display element and a method for manufacturing a liquid-crystal display element wherein the achievement of thinness is facilitated and it is possible to achieve an improvement in yield and quality.

SUMMARY OF THE INVENTION

In order to achieve the above-noted object, the present invention has the following basic technical constitution.

Specifically, in a liquid-crystal display element according to one aspect of the present invention, an array substrate on which a plurality of liquid-crystal injection areas are arranged and each liquid-crystal injection area is surrounded by a seal having an aperture and the an overall liquid-crystal injection areas being surrounded by an outer peripheral seal having an aperture, and an opposing substrate are adhered together, the aperture of the outer peripheral seal being sealed by a hole sealant, and a surface of at least one of the array substrate and the opposing substrate being polished with a polishing material, and thereafter, an end portion of at least either one of the array substrate and the opposing substrate being polished with end polishing operation so as to remove residual polishing material therefrom, after which cutting plurality of liquid-crystal injection areas along lines as formed between the opposite the aperture holes so as to separate individual liquid-crystal injection areas.

In this aspect of the present invention, a plurality of the apertures of the outer peripheral seal are provided along the outer peripheral seal and at crossing points each being formed between the outer peripheral seal and a line along which the individual liquid-crystal injection areas are cut apart.

In this aspect of the present invention, it is possible inject liquid crystal into each individual injection area, seal the areas, and adhere polarizers after the individual liquid crystal injection areas are separated.

09621450.072100

The seal and outer peripheral seals can be made of an epoxy resin, the hole sealant can be a UV-curing acrylic resin, and the polishing material can be an alumina polishing material.

A method for manufacturing a liquid-crystal display element according to another aspect of the present invention comprising, a first step of forming a plurality of liquid-crystal injection areas surrounded with a seal on an array substrate, a second step of adhering the array substrate on which overall the liquid-crystal injection areas being surrounded by an outer peripheral seal having an aperture and an opposing substrate, a third step of sealing the aperture of the outer peripheral seal using a hole sealant, a fourth step of polishing a surface of at least one of the array substrate and the opposing substrate using a polishing material, a fifth step of polishing an end surface of at least one of the array substrate and the opposing substrate, using a polishing material and removing the polishing material, and a sixth step of cutting the liquid-crystal injection areas along a virtual lines each formed between the apertures each provided on two of the outer peripheral seals, respectively, and each of the outer peripheral seals being oppositely arranged to each other.

The second step thereabout can include a seventh step of providing a plurality of the apertures being provided along each one of the outer peripheral seals and at crossing points each being formed between the outer peripheral seal and a virtual line along which the individual liquid-crystal injection areas would thereafter be cut apart.

The sixth step can include an eighth step of injecting liquid crystal into each liquid-crystal injection area, sealing the hole, and adhering a polarizer.

The first step can include a ninth step of forming a seal using an epoxy resin, the second step can include a tenth step of forming an outer peripheral seal using an epoxy resin, and the third step can include an eleventh

09521450.072100

step of forming a hole sealant with a UV-curing acrylic resin.

The fourth step can include a twelfth step of performing polishing using an alumina polishing material, a thirteenth step of performing lapping, and a fourteenth step of performing final polishing, and the fifth step can include a fifteenth step of chamfering the polished end surface.

In a liquid-crystal display element and a method for manufacturing a liquid-crystal display element according to the present invention, an array substrate on which a plurality of liquid-crystal injection areas surrounded with a seal and the overall liquid-crystal injection areas being surrounded by an outer peripheral seal are provided and an opposing substrate are adhered together, the aperture of the outer peripheral seal being sealed by a hole sealant, and the surface of at least one of a surface of the array substrate and the opposing substrate being polished with a polishing material and further an end portion thereof is also polished so that the polishing material is removed, after which cutting along the aperture is done to separate the individual liquid-crystal injection areas.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view showing an embodiment of a liquid-crystal display element according to the present invention.

Fig. 2 is a process diagram showing the manufacturing process for the liquid-crystal display element of Fig. 1.

Fig. 3 is a plan view showing the pattern construction of Fig. 1.

Fig. 4 is a cross-sectional view along the direction A-A' indicated in Fig. 3.

Fig. 5 is a cross-sectional view along the direction B-B' indicated in Fig. 3.

Fig. 6 is a process diagram showing the manufacturing process for a liquid-crystal display element of the past.

Fig. 7 is a plan view with a partial cutaway of a liquid-crystal

09521450-072100

display element manufacturing by the manufacturing method of Fig. 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention are described in detail below, with references made to relevant accompanying drawings.

Fig. 1 is a cross-sectional view showing an embodiment of a liquid-crystal display element according to the present invention, Fig. 2 is a process diagram showing a method for manufacturing the liquid-crystal display element of Fig. 1, Fig. 3 is a plan view of the pattern structure of the seal of Fig. 1, Fig. 4 is an A-A' cross-sectional view of Fig. 3, and Fig. 5 is a B-B' cross-sectional view of Fig. 3.

The liquid-crystal display element shown in Fig. 1 is made up of an oriented array substrate 10 and an opposing array 11, which are adhered by an epoxy resin seal 12.

A spacer 14 is disposed between the array substrate 10 and the opposing substrate 11 having spacers 14 disposed between the array substrate 10 and the opposing substrate 11 so as to maintain a uniform panel gap therebetween.

A liquid crystal 15 is sandwiched by the array substrate 10 and the opposing substrate 11. A polarizer 16 is adhered to the outer surface of the array substrate 10 and the opposing substrate 11.

In this case, a liquid crystal injection hole 17, to be described below, is provided in the seal 12.

After injecting the liquid crystal from the liquid crystal injection hole 17, the liquid crystal injection hole 17 is sealed by an acrylic resin, thereby holding the liquid crystal 15 therewithin. In these drawings, the reference numeral 13 denotes an orientation material, and 22 denotes color filters.

A liquid-crystal display element such as described above is manufactured as follows.

Specifically, as shown in Fig. 2, an array substrate 10 formed by

007220 09472960

performing a prescribed orientation operation and seal patterning and an opposing substrate 11 that is oriented and is treated so that a uniform panel gap is maintained are adhered together (step 201).

Next, after hole sealing so that polishing material is not intruded between the array substrate 10 and the opposing substrate 11, which are two glass substrates, the surface of at least one of the glass substrates is polished, and then the end surface is also polished, so as to make the thickness of the two glass substrates small (steps 202 to 204).

After the above, the individual liquid-crystal display elements are cut apart, the liquid crystal is injected into the element, the holes are sealed, and the polarizers are adhered, thereby completing the liquid-crystal display elements (steps 205 to 208).

The seal pattern structure is shown in Fig. 3 to Fig. 5.

A pattern for seals 12 which are provided liquid crystal injection holes 17, corresponding to each individual liquid-crystal display element, and a pattern for an outer peripheral seal 18 for preventing the intrusion of polishing material at the outer periphery are formed on the array substrate 10.

The seal material for the seal 12 and the outer peripheral seal 18 is an epoxy resin. The outer peripheral seal 18 is provided with a number of apertures 19 corresponding to the number of liquid-crystal display elements to be separated, on the virtual line along which they are to be cut apart.

Adhering the array substrate 10 and the opposing substrate 11, onto which is distributed the spacers 14, which maintain the panel gap uniformly, heat treating is done at a temperature of 160 °C, so as to harden the seal 12 and the outer peripheral seal 18.

When the above is done, because the apertures 19 of the outer peripheral seal 18 maintains the air pressures inside and outside the outer peripheral seal 18 at the same pressure, breakage of the seal pattern does not occur. Next, a hole sealant 20 made of a UV-curing acrylic resin is used to seal

007220-0942950

the apertures 19, this being subjected to UV radiation to harden the resin.

After the above, the surface of at least one of the two adhered glass substrates is polished. The polishing is done using an alumina-based polishing material with a grit diameter of approximately $10\ \mu\text{m}$ and, after lapping the panel thickness down from 1.4 mm to approximately 1.05 mm, a cerium oxide based polishing material having a grain diameter of approximately $1\ \mu\text{m}$ is used to perform polishing down to a panel thickness of approximately 1.0 mm.

The polishing force used is approximately 150 to 200 g/cm², and a water washing is done after polishing.

Next, in order to remove polishing material from the end parts of the two glass substrates, the end surfaces are polished. When this is done, as shown in Fig. 4 and Fig. 5, the end surfaces are processed so as to achieve a curved surface thereat, with the two glass substrates adhered together. After polishing the end surfaces, water washing is done.

In a liquid-crystal display element formed as described above, the pattern structure of the outer peripheral seal 18 is such that there is no intrusion of polishing material, and also so that apertures 19 are provided on extensions of the lines along which the individual liquid-crystal display element are cut apart.

Thus, by performing end surface polishing, there is total prevention of introduction of the polishing material 21 into the next process step, and also prevention of bad cutting at the cutting process step.

This is described below in further detail, with reference made to Fig. 4 and Fig. 5.

Fig. 4 shows the condition in which the remaining polishing material 21 is removed by end polishing. By removing the remaining polishing material, it is not introduced into the next process step, so that it does not contaminate the manufacturing apparatus in subsequent steps.

Also prevented are problems such as polishing material 21 intruding

between the glass substrates (Fig. 1) so as to cause poor orientation or prevent proper application of voltage across the liquid crystal 15.

When the cutting apart is done, the hole sealant 20 on the line along the cutting line B-B' of Fig. 3 is traversed in making the cut. Because the hole sealant 20, in contrast to the epoxy resin used in the outer peripheral seal 18, is a soft acrylic resin, there is no particular stress applied to the glass substrates when the cutting is done, so that there is prevention of bad scribing and breaking.

In this embodiment of the present invention, therefore, each liquid-crystal injection area is surrounded by a seal 12, and the overall liquid-crystal injection area is surrounded by an array substrate 10 and an opposing substrate 11 surrounded by an outer peripheral seal 18 having apertures 19, the apertures 19 of the outer peripheral seal 18 being sealed by a hole sealant 20, and the surface of at least on of the array substrate 10 and the opposing substrate 11 being polished with a polishing material 21, which is then removed, after which cutting along the apertures is done to separate the individual liquid-crystal injection areas, and in so doing to eliminate residual polishing material 21 caused by bad cutting, thereby enabling facilitating the achievement of a thin liquid-crystal display element and improving the yield and the quality thereof.

Although the above-noted embodiment of the present invention was described for the example in which the thicknesses of the array substrate 10 and opposing substrate 11, which are glass substrates is made thin by polishing, it will be readily understood that the present invention is not restricted in this manner, and can be applied as well to a case in which, for example, the thickness of the array substrate 10 and the opposing substrate 11 is made thin by etching.

Additionally, it will be understood that the liquid-crystal display element of the present invention is not restricted to an active matrix array

007220 09472950

such as a TFT or MIM type, but can also be applied to a liquid-crystal display using a drive method such as that of a simple matrix display or a segment display as well.

A separate embodiment of the present invention from those as mentioned above, will be explained hereunder with reference to Figs. 3 to 5.

In this embodiment, a liquid-crystal display element array is provided and as shown in Fig. 3, the liquid-crystal display element array of this embodiment comprises an array substrate 10 and an opposing substrate 11 and a plurality of liquid-crystal injection areas 30, each being surrounded by a seal 12 having an aperture 17 and the an overall liquid-crystal injection areas 30 being further surrounded by an outer peripheral seal 18 having apertures 19 sealed with a hole sealant 20, both of which being formed between the array substrate 10 and the opposing substrate 11, wherein at least a surface of either one of the array substrate and the opposing substrate being polished and at least an end portion of either one of the array substrate and the opposing substrate being polished, and further wherein a plurality of the apertures 19 being provided along each one of the outer peripheral seals 18-1 to 18-4 and at crossing points P each being formed between the outer peripheral seal 18 and a virtual line 40 along which the individual liquid-crystal injection areas 30 would thereafter be cut apart.

In this embodiment, the end portion of of either one of the array substrate and the opposing substrate showing a tapered configuration.

According to the liquid-crystal display element and method for manufacturing a liquid-crystal display element according to the present invention as described in detail above, by adopting a constitution in which each liquid-crystal injection area is surrounded by a seal, and the overall liquid-crystal injection area is surrounded by an array substrate and an opposing substrate surrounded by an outer peripheral seal having an aperture and are adhered together, the aperture of the outer peripheral seal being sealed by a

09621450-072100

hole sealant, and the surface of at least one of the array substrate and the opposing substrate being polished with a polishing material, which is then removed, after which cutting along the aperture is done to separate the individual liquid-crystal injection areas, the achievement of a thin liquid-crystal display element is facilitated, and it is possible to improve both liquid-crystal display element quality and yield.

007240" 09472950

What is claimed is:

1. A liquid-crystal display element wherein an array substrate on which a plurality of liquid-crystal injection areas are arranged and each liquid-crystal injection area is surrounded by a seal having an aperture and said an overall liquid-crystal injection areas being surrounded by an outer peripheral seal having an aperture, and an opposing substrate are adhered together, said aperture of the outer peripheral seal being sealed by a hole sealant, and a surface of at least one of said array substrate and said opposing substrate being polished with a polishing material, and thereafter, an end portion of at least either one of said array substrate and said opposing substrate being polished with end polishing operation so as to remove residual polishing material therefrom, after which cutting plurality of liquid-crystal injection areas along lines as formed between the opposite said aperture holes so as to separate individual liquid-crystal injection areas.
2. A liquid-crystal display element according to claim 1, wherein a plurality of said apertures of said outer peripheral seal are provided along said outer peripheral seal and at crossing points each being formed between said outer peripheral seal and a line along which said individual liquid-crystal injection areas are cut apart.
3. A liquid-crystal display element according to claim 1, wherein after separating an individual liquid-crystal injection area, liquid crystal is injected into said liquid-crystal injection area, hole sealing is performed, and a polarizer is adhered thereto.
4. A liquid-crystal display element according to claim 1, wherein said seal and outer peripheral seal comprise an epoxy resin, and further wherein said hole sealant comprises UV-curing acrylic resin and further wherein said polishing material is alumina polishing material.
5. A liquid-crystal display element array which comprises an array substrate and an opposing substrate and a plurality of liquid-crystal injection

001220 0912960

areas, each being surrounded by a seal having an aperture and said an overall liquid-crystal injection areas being further surrounded by an outer peripheral seal having apertures sealed with a hole sealant, both of which being formed between said array substrate and said opposing substrate, wherein at least a surface of either one of said array substrate and said opposing substrate being polished and at least an end portion of either one of said array substrate and said opposing substrate being polished, and further wherein a plurality of said apertures of said outer peripheral seal being provided along each one of said outer peripheral seals and at crossing points each being formed between said outer peripheral seal and a virtual line along which said individual liquid-crystal injection areas would thereafter be cut apart.

6. A liquid-crystal display element array according to claim 5, wherein said end portion of of either one of said array substrate and said opposing substrate showing a tapered configuration.

7. A method for manufacturing a liquid-crystal display element comprising:

a first step of forming a plurality of liquid-crystal injection areas surrounded with a seal on an array substrate;

a second step of adhering said array substrate on which overall said liquid-crystal injection areas being surrounded by an outer peripheral seal having an aperture and an opposing substrate;

a third step of sealing said aperture of said outer peripheral seal using a hole sealant;

a fourth step of polishing a surface of at least one of said array substrate and said opposing substrate using a polishing material;

a fifth step of polishing an end surface of at least one of said array substrate and said opposing substrate, using a polishing material and removing said polishing material; and

a sixth step of cutting said liquid-crystal injection areas along a

09621460-072100

virtual lines each formed between said apertures each provided on two of said outer peripheral seals, respectively, and each of said outer peripheral seals being oppositely arranged to each other.

8. A method for manufacturing a liquid-crystal display element according to claim 7, wherein said second step includes a seventh step of providing a plurality of said apertures being provided along each one of said outer peripheral seals and at crossing points each being formed between said outer peripheral seal and a virtual line along which said individual liquid-crystal injection areas would thereafter be cut apart.

9. A method for manufacturing a liquid-crystal display element according to claim 7, wherein said sixth step includes an eighth step of injecting liquid crystal into each said liquid-crystal injection area, sealing said hole, and adhering a polarizer.

10. A method for manufacturing a liquid-crystal display element according to claim 7, wherein:

said first step includes a ninth step of forming a seal using an epoxy resin;

said second step includes a tenth step of forming an outer peripheral seal using an epoxy resin; and

said third step includes an eleventh step of forming a hole sealant with a UV-curing acrylic resin.

11. A method for manufacturing a liquid-crystal display element according to claim 7, wherein said fourth step includes:

a twelfth step of performing polishing using an alumina polishing material;

a thirteenth step of performing lapping; and

a fourteenth step of performing final polishing,

and wherein said fifth step includes a fifteenth step of chamfering the polished end surface.


007220 09472960

ABSTRACT OF THE DISCLOSURE


In a liquid-crystal display element each individual liquid-crystal injection area is surrounded by a seal, and the overall liquid-crystal injection area is surrounded by an array substrate and an opposing substrate surrounded by an outer peripheral seal having an aperture and are adhered together, the aperture of the outer peripheral seal being sealed by a hole sealant, and the surface of at least one of the array substrate and the opposing substrate being polished with a polishing material, which is then removed, after which cutting along the aperture is done to separate the individual liquid-crystal injection areas, thereby facilitating the achievement of a thin liquid-crystal display element, while improving the quality and yield thereof.

09621460 072100


Fig. 1



F i g . 2




F i g . 3



001220" 09472960

F i g . 4



F i g . 5




Fig. 6





Fig. 7



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

LIQUID-CRYSTAL DISPLAY ELEMENT AND METHOD FOR MANUFACTURING SAME

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known by me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

NUMBER	COUNTRY	DAY/MONTH/YEAR FILED	PRIORITY CLAIMED
208450/1999	Japan	23/07/1999	YES

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

APPLICATION NO.	FILING DATE

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is known by me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

APPLICATION SERIAL NO.	FILING DATE	STATUS: PATENTED, PENDING, ABANDONED

I hereby appoint as my attorneys, with full powers of substitution and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Stephen A. Bent, Reg. No. 29,768; David A. Blumenthal, Reg. No. 26,257; William T. Ellis, Reg. No. 26,874; John J. Feldhaus, Reg. No. 28,822; Patricia D. Granados, Reg. No. 33,683; John P. Isacson, Reg. No. 33,715; Donald D. Jeffery, Reg. No. 19,980; Eugene M. Lee, Reg. No. 32,039; Richard Linn, Reg. No. 25,144; Peter G. Mack, Reg. No. 26,001; Brian J. McNamara, Reg. No. 32,789; Sybil Meloy, Reg. No. 22,749; George E. Quillin, Reg. No. 32,792; Colin G. Sandercock, Reg. No. 31,298; Bernhard D. Saxe, Reg. No. 28,665; Charles F. Schill, Reg. No. 27,590; Richard L. Schwaab, Reg. No. 25,479; Arthur Schwartz, Reg. No. 22,115; Harold C. Wegner, Reg. No. 25,258.

Address all correspondence to FOLEY & LARDNER, Washington Harbour, 3000 K Street, N.W., Suite 500, P.O. Box 25696, Washington, D.C. 20007-8696. Address telephone communications to _____ at (202) 672-5300.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of First or Sole Inventor Hirofumi KAMOSAWA	Signature of First or Sole Inventor <i>Hirofumi Kamosawa</i>	Date May 31, 2000
Residence Address Tokyo, Japan	Country of Citizenship Japan	
Post Office Address c/o NEC CORPORATION, 7-1, Shiba 5-chome, Minato-ku, Tokyo, Japan		

Full Name of Second Inventor Takeya SHIMIZU	Signature of Second Inventor <i>Takeya Shimizu</i>	Date May 31, 2000
Residence Address Tokyo, Japan	Country of Citizenship Japan	
Post Office Address c/o NEC CORPORATION, 7-1, Shiba 5-chome, Minato-ku, Tokyo, Japan		

Full Name of Third Inventor	Signature of Third Inventor	Date
Residence Address	Country of Citizenship	
Post Office Address		

Full Name of Fourth Inventor	Signature of Fourth Inventor	Date
Residence Address	Country of Citizenship	
Post Office Address		

Full Name of Fifth Inventor	Signature of Fifth Inventor	Date
Residence Address	Country of Citizenship	
Post Office Address		